

fuse ORBITUMTM

STAPLE SYSTEM

***True Bone
Compression***



9X | More
COMPRESSION

5X | Greater
PULL OUT
Resistance

Than nitinol staples


* Independent lab data on file with Fuse Medical

Compression Staple System



A NEW WAY TO COMPRESS

- **Multi-axial mechanical compression**
- **Unique delivery system** for soft and hard bone
- **Enhanced geometries** for superior bone purchase
- **5X greater pull-out resistance** than comparable staples
- **Titanium Ti-6AL-4V-ELI**, appropriate for nickel sensitive patients




Surgical Technique



STEP 1 - Implant Size Selection

Use Intraoperative Sizer to determine appropriate size, position, orientation and configuration of staple.



STEP 2 - Hole Preparation - Punch Method

Use corresponding size Punch for implant selected. Align points for desired orientation of the implant. Mallet the Punch to pierce the cortex with the points.

Optional Drill Method - Instead of Punch, use Drill to pierce the cortex through all holes required in corresponding size Drill Template.



STEP 3 - Initial Insertion

Load staple onto corresponding size Inserter. Align legs with the pre-drilled holes in the previously determined orientation. Impact Inserter with mallet until monocortical spikes make contact with the bone. Remove inserter.




STEP 4 - Final Seating

Perform final seating using the Tamp, mating the tapered nose of the Tamp with chamfer of the implant's center hole, or by tapping around bridge of the implant with Tamp until implant firmly enters the bone.

Staple Dimensions

ALL DIMENSIONS IN MILLIMETERS


Orbitum X (Round)



Part Number	Product Description
FO-1000-1208	Orbitum X Round Staple, 12mm
FO-1000-1610	Orbitum X Round Staple, 16mm
FO-1000-2012	Orbitum X Round Staple, 20mm
FO-1000-2414	Orbitum X Round Staple, 24mm

Outer Diameter	12	16	20	24
Bridge Thickness	1.0	1.05	1.30	1.50
Long Leg Length	7.95	10.55	12.95	15.38
Short Leg Length	4.2	5.55	6.70	7.78
Long Leg Thickness (width x depth)	1.1 X 1.0	1.4 X 1.05	1.75 X 1.3	1.97 X 1.50
Short Leg Thickness (width x depth)	1.25 X 1.0	1.65 X 1.05	2.05 X 1.3	2.45 X 1.50

Orbitum VI (Hourglass)



FO-1001-1208	Orbitum X Hourglass Staple, 12mm
FO-1001-1610	Orbitum X Hourglass Staple, 16mm
FO-1001-2012	Orbitum X Hourglass Staple, 20mm
FO-1001-2414	Orbitum X Hourglass Staple, 24mm

Diameter (outer x inner)	12 X 8	16 X 10.7	20 X 13.35	24 X 16
Bridge Thickness	1.35	1.35	1.35	1.35
Long Leg Length	7.5	10	12.5	15
Short Leg Length	3.75	5	6.25	7.50
Long Leg Thickness (width x depth)	1.1 X 1.0	1.4 X 1.05	1.75 X 1.3	1.97 X 1.50
Short Leg Thickness (width x depth)	1.25 X 1.0	1.65 X 1.05	2.05 X 1.3	2.45 X 1.50

Fuse Medical, Inc.

4343 Sigma Rd. Ste 500
Farmers Branch, TX 45244
469.862.3030

BRO-FOS001 Rev E
DC-0334

info@fusemedical.com
www.fusemedical.com

"Pat. No. 9,649,108; D 851250; Other Patents Pending".

Compression Staple System